ICM Manual De-Carbonising

Malcolm Horner BSc PhD FICE FRSE Hon FRIAS Chairman, Whole Life Consultants Ltd Emeritus Professor of Engineering Management, University of Dundee

ICMS INTERNAT



Principal changes between ICMS 2 and 3


- As little change as possible
- Extended to include Carbon Emissions
- Cost Categories, Groups and Sub-Groups changed to
- Categories, Groups and Sub-Groups
- Incorporates five new project types
- Additions and extensions to Categories, Groups, Sub-Groups and attributes for new project types
- Ditto for Railways

ICM


• Other minor amendments



ICMS 2 – Relationship between ICMS, Life Cycle Costs (LCC) and Whole Life Costs (WLC)










New project types

- Offshore structures
- Near shore works
- Ports
- Waterway works
- Land formation and reclamation





The Railway Corridor



6 Four foot : Standard interval between running rails of standard gauge track E

Six foot : Standard interval between a pair of tracks

(a)

d Ten foot : Standard interval between groups of tracks



Changes to Railways

- Added Sub-Groups "Control systems" and "Signalling"
- New attribute "operational telecommunications system" with the values "fixed telephone network I other stated"
- New attribute "ruling gradient"





ICMS To compare like withlike there is no alternative

Malcolm Horner BSc PhD FICE FRSE Hon FRIAS Chairman, Whole Life Consultants Ltd Emeritus Professor of Engineering Management, University of Dundee

ICMS INTERNAT